

jquery

<https://releases.jquery.com/>

datepicker

fuentes

- <https://bootstrap-datepicker.readthedocs.io/en/latest/options.html>
- <https://uxsolutions.github.io/bootstrap-datepicker/?#sandbox>
- <https://gijgo.com/datepicker/example/bootstrap-4>
- <https://stackoverflow.com/questions/25874375/multiple-dates-in-bootstrap-date-picker>

ejemplo

```
<script>
    $('#date').datepicker({
        uiLibrary: 'bootstrap4',
        minDate: '01/01/2020',
        maxDate: '31/12/2020',
        maxViewMode: 'months',
        multiselect: true,
        multiselectSeparator: ',',
        autoclose: false,
        language: 'ca',
        datesDisabled: ['02/06/2020', '02/21/2020'],
        format: 'dd/mm/yyyy'
    });
</script>
<script src="https://code.jquery.com/jquery-3.3.1.min.js"></script>
<script
src="https://cdnjs.cloudflare.com/ajax/libs/bootstrap-datepicker/1.8.0/js/bootstrap
-datepicker.js"></script>
<link
href="https://cdnjs.cloudflare.com/ajax/libs/bootstrap-datepicker/1.8.0/css/bootstr
ap-datepicker.css" rel="stylesheet"/>
<input type="text" id="date">
```

petición AJAX y modificación DOM

- bootstrap
 - custom-control-input
 - toast
- DataTable

```
$(document)
    .ready(function () {

        $('#recorda').toast('show');
```

```

$( '#tablecontrols' ).DataTable({
    paging: false,
    ordering: false,
    select: true
});

$( '.dataTables_length' ).addClass( 'bs-select' );

$( 'td[data-href]' ).on( 'click', function() {
    window.location = ( $(this).data("href") );
    //window.open( $(this).data("href"), "_blank" );
});

$( "input:checkbox" ).on( 'change', function() {

    inputObject = $(this);
    clase = ( $(this).val() == "1" ) ? 'table-success' : 'table-danger';
    id = $(this).attr( 'data-ajax-id' );
    field = $(this).attr( 'data-ajax-field' );
    isChecked = $(this).is( ":checked" );
    isValue = ( isChecked ) ? 1 : 0;
    datos = {
        'id': id,
        'field': field,
        'value': isValue
    };
    ajaxError = 0;

    $( '#desant' ).toast( 'show' );

    jQuery.ajax({
        type: 'post',
        url: '/controller/controls/update-list-checks.php',
        data: datos,
        success: function( resp ) {
            $( '#desant' ).toast( 'hide' );
            if ( isChecked ) $(inputObject).parents( 'tr' ).addClass( clase );
            else $(inputObject).parents( 'tr' ).removeClass( clase );
            $( '#desat' ).toast( 'show' );
        },
        error: function( xhr, status, error ) {
            $( '#desant' ).toast( 'hide' );
            $( '#error' ).toast( 'show' );
            $(inputObject).prop( 'checked', !isChecked );
        },
        dataType: 'json'
    });

});
});

```

```

<script type="text/javascript"
src="https://cdn.datatables.net/1.10.20/js/jquery.dataTables.min.js"></script>
<script type="text/javascript"
src="https://cdn.datatables.net/1.10.20/js/dataTables.bootstrap4.min.js"></script>

```

```

<div id="desant" class="toast" role="alert" aria-live="assertive" aria-
atomic="true"
    style="position: absolute; top: 9rem; right: 1rem;">
    <div class="toast-header">
        <span class="badge badge-warning">&nbsp;&nbsp;&nbsp;</span>
        <strong class="mr-auto">&nbsp;&nbsp;&nbsp;Atenció!</strong>
        <button type="button" class="ml-2 mb-1 close" data-dismiss="toast"
aria-label="Close">
            <span aria-hidden="true">&times;</span>
        </button>
    </div>
    <div class="toast-body">
        S'estàn desant les dades...
    </div>
</div>

<div id="desat" class="toast" role="alert" aria-live="assertive" aria-
atomic="true" data-delay="2000"
    style="position: absolute; top: 9rem; right: 1rem;">
    <div class="toast-header">
        <span class="badge badge-success">&nbsp;&nbsp;&nbsp;</span>
        <strong class="mr-auto">&nbsp;&nbsp;&nbsp;Atenció!</strong>
        <button type="button" class="ml-2 mb-1 close" data-dismiss="toast"
aria-label="Close">
            <span aria-hidden="true">&times;</span>
        </button>
    </div>
    <div class="toast-body">
        Les dades s'han desat correctament
    </div>
</div>

<td class="text-center align-middle">
    <div class="custom-control custom-switch mb-3">
        <input type="checkbox" data-ajax-
id="<?=$element['id']?>" data-ajax-field="exclos" class="custom-control-input"
id="exclos<?=$element['id']?>" name="exclos<?=$i?>" value="2"
<?=( $element['exclos'] == 1 ) ? 'checked' : ''?>
        <label class="custom-control-label"
for="exclos<?=$element['id']?>">&nbsp;&nbsp;&nbsp;</label>
    </div>
    <!--input type="checkbox" name="exclos" value="1"
<?=( $element['exclos'] == 1 ) ? 'checked' : ''?> /-->
</td>

```

```

<?php
session_start();
// http://www.faqs.org/rfcs/rfc2616.html

require_once "../../config.php";
require_once $BASE_PATH."www/model/model-controls.php";

$codRetronDesc = array(
    0 => 'operació realitzada correctament',
    1 => 'error en els paràmetres enviats'

```

```
);  
$fieldsPermesos = array('exclos','ressonat');  
  
$codRetorn = 0;  
  
$id = ( array_key_exists('id',$_POST) ) ? $_POST['id'] : 0;  
$field = ( array_key_exists('field',$_POST) ) ? $_POST['field'] : '';  
$value = ( array_key_exists('value',$_POST) ) ? $_POST['value'] : '';  
  
if ( (array_search($field,$fieldsPermesos))!== false ) {  
    $data = array(  
        'id' => $id,  
        $field => $value  
    );  
    updateControl($data);  
    $headerRetorn = 'HTTP/1.1 200 OK';  
} else {  
    $codRetorn = 1;  
    $headerRetorn = 'HTTP/1.1 406 Not Acceptable';  
}  
  
$arrRespuesta = array(  
    "status" => $codRetorn,  
    "txt" => $codRetronDesc[$codRetorn]  
);  
  
header($headerRetorn);  
header('Content-Type: application/json; charset=UTF-8');  
echo json_encode($arrRespuesta);  
  
?>
```

From:

<https://matebcn.eu/> - miguel angel torres egea

Permanent link:

<https://matebcn.eu/development:jquery:start>Last update: **21/05/2026 12:00**