

java

debian 8, jre 8

- <http://openjdk.java.net/install/>
- <https://wiki.debian.org/JavaPackage>

instalación

- `$ sudo apt-get install default-jre`
- `$ sudo apt-get install default-jdk`
- `$ sudo apt-get install openjdk-7-jre`
- `sudo apt-get install python-software-properties sudo add-apt-repository ppa:webupd8team/java sudo apt-get update`
- `$ sudo apt-get install oracle-java7-installer`
- `$ sudo apt-get install oracle-java8-installer`
- `$ sudo apt-get install oracle-java8-set-default`

seleccionar versión

- `$ sudo update-alternatives --config java`
 - permite seleccionar de las versiones instaladas cual usará usada por defecto

variable de entorno

1. buscar la ruta: `$ sudo update-alternatives --config java`
2. modificar la variable de entorno: `$ sudo vim /etc/environment`
 - `JAVA_HOME`
3. recargar `$ source /etc/environment`

desinstalar

- mirar las rutas existentes
- `$ sudo update-alternatives --remove «java» «/usr/lib/jvm/jdk1.7.0_04/bin/java»`
- `$ cd /usr/lib/jvm`
- `$ sudo rm -rf jdk1.7.0_04`
- `$ sudo dpkg --get-selections | grep -i jdk`
- `$ sudo apt-get purge icedtea-* openjdk-*`
- `$ sudo dpkg --get-selections | grep -i jdk`

From:
<https://matebcn.eu/> - miguel angel torres egea

Permanent link:
<https://matebcn.eu/linux:paquetes:java:start>

Last update: 03/04/2020 20:03



