.git*

git

- .git* - .gitattributes
- .git* - .gitignore

.gitconfig

- `~/.gitconfig`:

```
[alias]
        ck = checkout
        s = status
        l = log --oneline --max-count=10
        ll = log --pretty=format:"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate --numstat
        lg = log --oneline --decorate --graph
        ls = log --pretty=format:"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate
        alias = ! git config --get-regexp ^alias\\. | sed -e s/^alias\\.// -e s/\\
/\\ =\\ /
        a = add
        b = branch
        c = commit
        bv = branch -avv
        lv = log --walk-reflogs --max-count=10
        ai = add --interactive
        ss = status --short
```

```
# https://gist.github.com/johnpolacek/69604a1f6861129ef088
[alias]
    co = checkout
    cob = checkout -b
    coo = !git fetch && git checkout
    br = branch
    brd = branch -d
    brD = branch -D
    merged = branch --merged
    st = status
    aa = add -A .
    cm = commit -m
    aacm = !git add -A . && git commit -m
    cp = cherry-pick
    amend = commit --amend -m
    dev = !git checkout dev && git pull origin dev
    staging = !git checkout staging && git pull origin staging
    master = !git checkout master && git pull origin
    po = push origin
    pod = push origin dev
    pos = push origin staging
    pom = push origin master
    poh = push origin HEAD
    pogm = !git push origin gh-pages && git checkout master && git pull origin
```

```
master && git rebase gh-pages && git push origin master && git checkout gh-pages
    pomg = !git push origin master && git checkout gh-pages && git pull origin gh-
pages && git rebase master && git push origin gh-pages && git checkout master
    plo = pull origin
    plod = pull origin dev
    plos = pull origin staging
    plom = pull origin master
    ploh = pull origin HEAD
    unstage = reset --soft HEAD^
    ls = log --pretty=format:"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate
    ll = log --pretty=format:"%C(yellow)%h%Cred%d\\ %Creset%s%Cblue\\ [%cn]" --
decorate --numstat
    f = "!git ls-files | grep -i"
    gr = grep -Ii
    la = "!git config -l | grep alias | cut -c 7-"
```

.gitkeep

Fichero vacío para indicar que ese directorio se ha de mantener, aunque no contenga más archivos.

From:
https://matebcn.eu/ - **miguel angel torres egea**

Permanent link:
https://matebcn.eu/tech:git:dotfiles

Last update: **13/07/2026 10:57**